

$26\,980\,243\,1$ TEMPESTA SYSTEM 250 SHOWER SYSTEM WITH DIVERTER FOR WALL MOUNTING



PRODUCT DESCRIPTION (1/2)

- · Colour: matte black
- · consisting of:
- · horizontal 390 mm shower arm, adjustable before installation
- change by diverter between hand shower, head shower or head shower
 Eco setting
- head shower Tempesta 250
- · 2 spray patterns (via diverter):
- · Rain, SmartRain
- · head shower with black rear cover
- · with ball joint
- · rotation angle ± 10°
- hand shower Tempesta 110
- · 3 spray patterns:
- · Rain, Jet, Massage
- adjustable in height with gliding element
- distance between diverter and upper bracket: 620 mm
- shower hose Relexaflex 1500 mm 1/2" x 1/2"
- shower hose Relexaflex 1250 mm 1/2 x 1/2"
- flexible installation: connection to faucet / wall union for water supply with 1/2" thread of the 1250 mm shower hose
- maximum flow rate (at 3 bar): 7.9 l/min
- GROHE Water Saving Less water, perfect flow
- GROHE SmartSwitch easily rotate the dial to enjoy your preferred spray option
- GROHE DreamSpray perfect spray pattern
- ShockProof silicone ring prevents damages caused by shower falling
- SpeedClean anti-lime system
- · Inner WaterGuide for a longer life
- suitable for instantaneous heaters from 18 kW/h



$26\,980\,243\,1$ TEMPESTA SYSTEM 250 SHOWER SYSTEM WITH DIVERTER FOR WALL MOUNTING

PRODUCT DESCRIPTION (2/2)

- minimum flow rate 7 l/min.
- minimum pressure 1.0 bar
- · professional edition